

Fuentes de Alimentación IP20



| Referencia <i>Reference</i> | W | Voltaje Entrada <i>Entry Voltage</i> | Voltaje Salida <i>Output Voltage</i> | Corriente Salida <i>Output Current</i> | Eficiencia <i>Efficiency</i> | Dimensiones <i>L/W/H/MM</i> | Material | Temp. de trabajo <i>Work temperature</i> |
|--------------------------------|------|---|---|---|---------------------------------|--------------------------------|----------|---|
| 80060 | 60W | 170-250VAC | 24V | 2.5A | 86% | 170 x 34 x 23 | Metal | -30°C a +50°C |
| 80061 | 100W | 170-250VAC | 24V | 4.2A | 86% | 140 x 49 x 29 | Metal | -30°C a +50°C |
| 80062 | 150W | 170-250VAC | 24V | 6.25A | 86% | 195 x 49 x 29 | Metal | -30°C a +50°C |
| 80063 | 200W | 170-250VAC | 24V | 8.3A | 86% | 195 x 49 x 29 | Metal | -30°C a +50°C |
| 80064 | 250W | 170-250VAC | 24V | 10.4A | 86% | 230 x 64 x 35 | Metal | -30°C a +50°C |



| Referencia <i>Reference</i> | W | Voltaje Entrada <i>Entry Voltage</i> | Voltaje Salida <i>Output Voltage</i> | Corriente Salida <i>Output Current</i> | Eficiencia <i>Efficiency</i> | Dimensiones <i>L/W/H/MM</i> | Material | Temp. de trabajo <i>Work temperature</i> |
|--------------------------------|------|---|---|---|---------------------------------|--------------------------------|----------|---|
| LRS-35-24 | 35W | 85-264VAC | 24V | 1.5A | 88% | 99 x 82 x 30 | Metal | -30°C a +70°C |
| LRS-50-24 | 50W | 85-264VAC | 24V | 2.2A | 88% | 99 x 82 x 30 | Metal | -30°C a +70°C |
| LRS-75-24 | 75W | 85-264VAC | 24V | 3.2A | 90% | 99 x 97 x 30 | Metal | -30°C a +70°C |
| LRS-100-24 | 100W | 85-264VAC | 24V | 4.5A | 90% | 129 x 97 x 30 | Metal | -30°C a +70°C |
| LRS-150-24 | 150W | 85-264VAC | 24V | 6.5A | 89% | 159 x 97 x 30 | Metal | -30°C a +70°C |



| Referencia <i>Reference</i> | W | Voltaje Entrada <i>Entry Voltage</i> | Voltaje Salida <i>Output Voltage</i> | Corriente Salida <i>Output Current</i> | Eficiencia <i>Efficiency</i> | Dimensiones <i>L/W/H/MM</i> | Material | Temp. de trabajo <i>Work temperature</i> |
|--------------------------------|-------|---|---|---|---------------------------------|--------------------------------|----------|---|
| RSP-200-24 | 200W | 88-264VAC | 24V | 8.4A | 89,5% | 215 x 115 x 30 | Metal | -30°C a +70°C |
| RSP-320-24 | 320W | 88-264VAC | 24V | 13.4A | 89% | 215 x 115 x 30 | Metal | -30°C a +70°C |
| RSP-500-24 | 500W | 85-264VAC | 24V | 21A | 89% | 230 x 127 x 40,5 | Metal | -30°C a +70°C |
| RSP-750-24 | 750W | 90-264VAC | 24V | 31.3A | 90,5% | 250 x 127 x 41 | Metal | -30°C a +70°C |
| RSP-1000-24 | 1000W | 90-264VAC | 24V | 40A | 88% | 295 x 127 x 41 | Metal | -30°C a +70°C |