



Referencia Reference	W	Voltaje Entrada Entry Voltage	Voltaje Salida Output Voltage	Corriente Salida Output Current	Eficiencia Efficiency	Dimensiones L/W/H/MM	Material	Temp. de trabajo Work temperature
80065	20W	100-240V	24V	0.84A	80%	143 x 30 x 23	Plástico	-30°C a +50°C
80066	36W	100-240V	24V	1.5A	80%	148 x 42 x 30	Plástico	-30°C a +50°C
80067	60W	100-240V	24V	2.5A	80%	166 x 43 x 34	Plástico	-30°C a +50°C
80068	75W	100-240V	24V	3.13A	80%	166 x 43 x 34	Plástico	-30°C a +50°C
80069	100W	100-240V	24V	4.2A	80%	192 x 53 x 36	Plástico	-30°C a +50°C



Referencia Reference	W	Voltaje Entrada Entry Voltage	Voltaje Salida Output Voltage	Corriente Salida Output Current	Eficiencia Efficiency	Dimensiones L/W/H/MM	Material	Temp. de trabajo Work temperature
80070	100W	90-264VAC	24V	4.17A	85%	182 x 62 x 17	Metal	-30°C a +50°C
80071	150W	176-264VAC	24V	6.25A	85%	198 x 58 x 32	Metal	-30°C a +50°C
80072	200W	176-264VAC	24V	8.3A	85%	238 x 58 x 32	Metal	-30°C a +50°C
80073	250W	176-264VAC	24V	10.5A	85%	228 x 72 x 32	Metal	-30°C a +50°C
80074	300W	176-264VAC	24V	12.5A	85%	228 x 72 x 32	Metal	-30°C a +50°C



Referencia Reference	W	Voltaje Entrada Entry Voltage	Voltaje Salida Output Voltage	Corriente Salida Output Current	Eficiencia Efficiency	Dimensiones L/W/H/MM	Material	Temp. de trabajo Work temperature
LPV-20-24	20W	90-264VAC	24V	0.84A	83%	118 x 35 x 26	Plástico	-30°C a +70°C
LPV-35-24	35W	90-264VAC	24V	1.5A	85%	148 x 40 x 30	Plástico	-30°C a +65°C
LPV-60-24	60W	90-264VAC	24V	2.5A	86%	162,5 x 42,5 x 32	Plástico	-30°C a +70°C
LPV-100-24	100W	90-264VAC	24V	4.2A	88%	190 x 52 x 37	Plástico	-25°C a +70°C
LPV-150-24	150W	180-305VAC	24V	6.3A	89%	191 x 63 x 37,5	Plástico	-25°C a +65°C



Referencia Reference	W	Voltaje Entrada Entry Voltage	Voltaje Salida Output Voltage	Corriente Salida Output Current	Eficiencia Efficiency	Dimensiones L/W/H/MM	Material	Temp. de trabajo Work temperature
ELG-200-24	200W	100-305VAC	24V	8.4A	92%	244 x 71 x 37,5	Metal	-40°C a +85°C
ELG-240-24	240W	100-305VAC	24V	10A	92%	244 x 71 x 37,5	Metal	-40°C a +85°C
ELG-300-24	300W	100-305VAC	24V	12.5A	93%	246 x 77 x 39,5	Metal	-40°C a +90°C