

# DOWNLIGHT ELLEN COLGANTE CARRIL BLANCO 20W 3000K 45° ORO DALI



|                            |               |
|----------------------------|---------------|
| <b>REFERENCIA</b>          | 61415CC450C   |
| <b>EAN-13</b>              | 8433973562947 |
| <b>CONSUMO</b>             | 20W           |
| <b>°K</b>                  | 3000K         |
| <b>COLOR ITEM</b>          | Blanco        |
| <b>MATERIAL PRODUCTO</b>   | Aluminio+PC   |
| <b>COLOR DIFUSOR</b>       | Oro           |
| <b>LUMENS/WATIO</b>        | 89Lm/W        |
| <b>LUMENS CHIP</b>         | 1780LM        |
| <b>CHIP</b>                | LUMINUS       |
| <b>NUMERO CHIPS</b>        | 1 PCS         |
| <b>DRIVER</b>              | HEP           |
| <b>VIDA UTIL</b>           | 30000H        |
| <b>FLICKER</b>             | No Flicker    |
| <b>%THD</b>                | ≤12%          |
| <b>FACTOR DE POTENCIA</b>  | PF ≥0.90      |
| <b>SDCM</b>                | <5            |
| <b>REGULACION</b>          | DALI          |
| <b>IP</b>                  | IP20          |
| <b>IK</b>                  | IK06          |
| <b>PROT.SOBRETENSIONES</b> | 1KV           |
| <b>ORIENTABLE</b>          | No            |
| <b>ANGULO APERTURA</b>     | 45°           |
| <b>TEMP. TRABAJO</b>       | -20°+45°      |
| <b>VOLTAJE SALIDA</b>      | AC200V-240V   |
| <b>VOLTAJE ENTRADA</b>     | 30-40,6V      |
| <b>FRECUENCIA</b>          | 50/60HZ       |
| <b>mA</b>                  | 500mA         |
| <b>CRI</b>                 | ≥90           |
| <b>UGR</b>                 | <16           |
| <b>DIAMETRO</b>            | 66mm          |
| <b>ALTURA</b>              | 310mm         |
| <b>PESO</b>                | 0,65Kg        |
| <b>GARANTIA</b>            | 5 AÑOS        |
| <b>CERTIFICADO</b>         | CE & RoHS     |

*Lighting with you*